

N15S MAX 200 W tri-colour + remote · purple cap

200 W · 48,000 lm · remote handset · 6000/4300/3000 K + strobe

|             |                 |                          |            |
|-------------|-----------------|--------------------------|------------|
| POWER       | LUMINOUS FLUX   | COLOUR TEMPERATURE       | WATERPROOF |
| 200 W / set | 48,000 lm / set | 6000 K · 4300 K · 3000 K | IP68       |

SPECIFICATION

| Field              | Value                                                        |
|--------------------|--------------------------------------------------------------|
| Fittings           | H1 · H3 · H4 · H7 · H8 · H9 · H11 · 9005 · 9006 · 9012 · D2H |
| Power              | 200 W / set (65 W per colour)                                |
| Voltage            | DC 8–60 V                                                    |
| Luminous flux      | 48,000 lm / set (manufacturer rating)                        |
| Colour temperature | 6000 K · 4300 K · 3000 K                                     |
| Colour switching   | Remote handset (included) + strobe                           |
| LED chips          | CSP8050                                                      |
| Cooling            | Triple copper heat pipe + dual copper substrate + fan        |
| Waterproof         | IP68                                                         |
| Lifespan           | 50,000 h                                                     |
| Rear cap           | Purple                                                       |
| Patent             | Design patent ZL202330622497.0                               |
| Unit packing       | 18 × 13.5 × 6 cm · 200 g (sold per single bulb)              |
| Retail             | 1 pc, shipped from stock                                     |
| Wholesale          | Mixed fittings per carton                                    |

NOTES

Luminous flux is the manufacturer rating taken from the factory's own product listing, not an independent photometric measurement; stabilised output after warm-up is typically lower. Where a value is not published by the factory it is left out rather than estimated.

ORDERING

|                      |                                               |
|----------------------|-----------------------------------------------|
| Minimum order        | 1 pc retail · 500 sets OEM / private label    |
| Production lead time | 25 days for OEM and bulk orders               |
| Warranty             | 12 months — defective units replaced          |
| Fitting mix          | Mixed bases inside one master carton          |
| Pricing              | On request — quoted against market and volume |